

XT Series HOLEMIKES

Die Quip XT series of mechanical and digital holemikes are a great method for accurately measuring die and tube inside diameters. Their a quick, easy and accurate method to measuring at machinery or in the quality lab. These internal micrometers are available between .080-12" (2-300mm) to fit your size requirements.



INCH MANUAL MICROMETERS

Range	Part No.	Set No.	Accuracy	Ring Gage
.080-.100"	52-255-305		.00015"	.1000"
.100-.120"	52-255-306	52-255-365	.00015"	.1000"
.120-.160"	52-255-307		.00015"	.1600"
.160-.200"	52-255-308		.00015"	.1600"
.200-.250"	52-255-309	52-255-465	.00015"	.2000"
.250-.312"	52-255-310		.00015"	.3120"
.312-.375"	52-255-311	52-255-565	.00015"	.3120"
.375-.500"	52-255-312		.00015"	.5000"
.500-.625"	52-255-313		.00015"	.5000"
.625-.750"	52-255-314	52-255-665	.00015"	.7500"
.750-1.000"	52-255-315		.00015"	.7500"
1.000-1.375"	52-255-316		.00015"	1.375"
1.375-2.000"	52-255-317	52-255-775	.00015"	1.375"
2.000-2.625"	52-255-318		.00015"	2.625"
2.625-3.250"	52-255-319		.00015"	2.625"
3.250-4.000"	52-255-320	52-255-885	.00015"	3.250"
4.000-5.000"	52-255-321		.00020"	5.000"
5.000-6.000"	52-255-322	52-255-890	.00020"	5.000"

INCH/METRIC DIGITAL MICROMETERS

Range	Part No.	Set No.	Accuracy	Ring Gage
.080-.100" (2-2.5mm)	54-366-003		.004mm	2.5mm
.100-.120" (2.5-3mm)	54-366-004		.004mm	2.5mm
.120-.160" (3-4mm)	54-366-005		.004mm	4mm
.160-.200" (4-5mm)	54-366-006		.004mm	4mm
.200-.250" (5-6mm)	54-366-007	54-364-000	.004mm	5mm
.250-.312" (6-8mm)	54-366-008		.004mm	8mm
.312-.375" (8-10mm)	54-366-010	54-364-010	.004mm	8mm
.375-.500" (10-12.5mm)	54-366-012		.004mm	12.5mm
.500-.625" (12.5-16mm)	54-366-014		.004mm	12.5mm
.625-.750" (16-20mm)	54-366-016	54-364-020	.004mm	20mm
.750-1.000" (20-25mm)	54-366-018		.004mm	20mm
1.000-1.375" (25-35mm)	54-366-020		.004mm	35mm
1.375-2.000" (35-50mm)	54-366-022	54-364-050	.004mm	35mm
2.000-2.625" (50-65mm)	54-366-024		.005mm	65mm
2.625-3.250" (65-80mm)	54-366-026		.005mm	65mm
3.250-4.000" (80-100mm)	54-366-028	54-364-100	.005mm	80mm
4.000-5.000" (100-125mm)	54-366-030		.006mm	125mm
5.000-6.000" (125-150mm)	54-366-032	54-364-105	.006mm	125mm

METRIC MANUAL MICROMETERS

Range	Part No.	Set No.	Accuracy	Ring Gage
2-2.5mm	52-255-405		.004mm	2.5mm
2.5-3mm	52-255-406	52-255-368	.004mm	2.5mm
3-4mm	52-255-407		.004mm	4mm
4-5mm	52-255-408		.004mm	4mm
5-6mm	52-255-409	52-255-468	.004mm	5mm
6-8mm	52-255-410		.004mm	8mm
8-10mm	52-255-411	52-255-568	.004mm	8mm
10-12.5mm	52-255-412		.004mm	12.5mm
12.5-16mm	52-255-413		.004mm	12.5mm
16-20mm	52-255-414	52-255-668	.004mm	20mm
20-25mm	52-255-415		.004mm	20mm
25-35mm	52-255-416		.004mm	35mm
35-50mm	52-255-417	52-255-768	.004mm	35mm
50-65mm	52-255-418		.005mm	65mm
65-80mm	52-255-419		.005mm	65mm
80-100mm	52-255-420	52-255-868	.005mm	80mm
100-125mm	52-255-421		.006mm	125mm
125-150mm	52-255-422	52-255-898	.006mm	125mm

All XT Holemikes Features

- Graduations .00025" (0.005mm)
- 3 point contact with tungsten carbide anvils above .5" (12.5mm)
- 2 point contact from .080-.375" (2-10mm)
- Ratchet stop for consistent measuring
- Extensions available for deep measuring
- Setting rings included in all sets
- Includes UKAS certificates for all Holemikes and setting rings
- Every gage is individually serialized

Additional Digital Features

- Resolution .00005" (0.001mm)
- Large easy to read swivel display
- RS-232C output
- Two preset memories
- Simple two button operation
- Direct inch/metric conversion

DIE QUIP CORP.

5360 Enterprise Blvd.
Bethel Park, PA 15102 USA
412/833-1662
412/835-6474 FAX
www.DIEQUIP.com
email - DIEQUIP@DIEQUIP.com