

# VALUE HOLEMIKES

Die Quip value series of mechanical and digital holemikes are a great method for accurately measuring die and tube inside diameters. Their a quick, easy and accurate method to measure at machinery or in the quality lab. These internal micrometers are available between .150-12" to fit your size requirements.



## INCH/METRIC DIGITAL MICROMETERS

| Range                       | Part No. | Set No.  | Accuracy         | Ring Gage |
|-----------------------------|----------|----------|------------------|-----------|
| .275-.350" (7-9mm)          | 13-541-8 |          | .0001" (0.003mm) | .3500"    |
| .350-.425" (9-11mm)         | 13-542-6 |          | .0001" (0.003mm) | .3500"    |
| .425-.500" (11-12.7mm)      | 13-543-4 | 13-555-8 | .0001" (0.003mm) | .5000"    |
| .500-.650" (12.7-16.5mm)    | 13-544-2 |          | .0001" (0.003mm) | .5000"    |
| .650-.800" (16.5-20.3mm)    | 13-545-9 | 13-556-6 | .0001" (0.003mm) | .6500"    |
| .800-1.000" (20.3-25.4mm)   | 13-546-7 |          | .0001" (0.003mm) | 1.000"    |
| 1.000-1.200" (25.4-30.5mm)  | 13-547-5 |          | .0001" (0.003mm) | 1.000"    |
| 1.200-1.600" (30.5-40.6mm)  | 13-548-3 |          | .0001" (0.003mm) | 1.600"    |
| 1.600-2.000" (40.6-50.8mm)  | 13-549-1 | 13-557-4 | .0001" (0.003mm) | 1.600"    |
| 2.000-2.500" (50.8-63.5mm)  | 13-550-9 |          | .0001" (0.003mm) | 2.500"    |
| 2.500-3.000" (63.5-76.2mm)  | 13-551-7 |          | .0001" (0.003mm) | 2.500"    |
| 3.000-3.500" (76.2-91.5mm)  | 13-552-5 |          | .0001" (0.003mm) | 3.500"    |
| 3.500-4.000" (91.5-101.6mm) | 13-553-3 | 13-558-2 | .0001" (0.003mm) | 3.500"    |

## INCH MANUAL MICROMETERS

| Range        | Part No. | Set No.  | Accuracy | Ring Gage |
|--------------|----------|----------|----------|-----------|
| .150-.175"   | 10-701-1 |          | .00015"  | .1750"    |
| .175-.225"   | 10-702-9 |          | .00015"  | .2250"    |
| .225-.275"   | 10-703-7 | 10-700-3 | .00015"  | .2250"    |
| .275-.350"   | 10-711-0 |          | .00015"  | .3500"    |
| .350-.425"   | 10-712-8 |          | .00015"  | .3500"    |
| .425-.500"   | 10-713-6 | 10-710-2 | .00015"  | .5000"    |
| .500-.650"   | 10-721-9 |          | .00015"  | .5000"    |
| .650-.800"   | 10-722-7 | 10-720-1 | .00015"  | .6500"    |
| .800-1.000"  | 10-731-8 |          | .00015"  | 1.000"    |
| 1.000-1.200" | 10-732-6 |          | .00015"  | 1.000"    |
| 1.200-1.400" | 10-733-4 |          | .00015"  | 1.400"    |
| 1.400-1.600" | 10-734-2 | 10-720-0 | .00015"  | 1.400"    |
| 1.600-2.000" | 10-741-7 |          | .00020"  | 2.000"    |
| 2.000-2.400" | 10-742-5 |          | .00020"  | 2.000"    |
| 2.400-2.800" | 10-743-3 |          | .00020"  | 2.800"    |
| 2.800-3.200" | 10-744-1 |          | .00020"  | 2.800"    |
| 3.200-3.600" | 10-745-8 |          | .00020"  | 3.600"    |
| 3.600-4.000" | 10-746-6 | 10-740-9 | .00020"  | 3.600"    |

### All XT Holemikes Features

- Graduations .0001"
- 3 point contact with tungsten carbide anvils
- Ratchet stop for consistent measuring
- Setting rings included in all sets

### Additional Digital Features

- Resolution .00005" (0.001mm)
- IP54 Protection
- SPC port outlet
- Individuals supplied with ring gage
- Simple two button operation
- Direct inch/metric conversion

**DIE QUIP CORP.**

5360 Enterprise Blvd.  
Bethel Park, PA 15102 USA  
412/833-1662  
412/835-6474 FAX  
[www.DIEQUIP.com](http://www.DIEQUIP.com)  
email - [DIEQUIP@DIEQUIP.com](mailto:DIEQUIP@DIEQUIP.com)